



G304H-2615-BCLPX

specifications

- 4 - 30 ton compression force (adjustable)
- 26 L-R x 15 F-B fully guided heated platens cored for cooling
- 800 F max operating temperature
- 4 daylight openings
- 6" open daylight (each opening)
- (2) 4" bore JIC style clamp cylinders
- 24 stroke
- 70 IPM closing speed
- 5 IPM pressing speed
- 75 IPM opening speed
- Weight: 7,800 lbs.
- Dimensions: 66" w x 46" d x 110" h

features

- Built-in lift truck tubes
- Allen Bradley MicroLogix 1200 programmable controller with PanelView 300 Micro operator interface
- Cycle counter through PLC
- Proximity switches to control "slow close" position and "cycle reset"
- Clamp pressure relief valve and gauge
- Automatic "bump" ("breathe") sequence
- Digital force readout
- Pressing speed control
- Automatic low pressure system
- Perimeter guarding with automatic operator gate



Wabash MPI

1569 Morris St., P.O. Box 298, Wabash, IN 46992-0298 USA

Phone: 260-563-1184 Fax: 260-563-1396

Email: wabashmpi@corpemail.com, Internet: www.wabashmpi.com

All data subject to change without notice © 2011 Wabash MPI

CARVER