



# P3H-15-CLX

## specifications

- Pneumatic clamp
- 1,000 lbs.- 3 ton compression force(adjustable)
- 15" L-R x 15" F-B fully guided heated platens
- 6" - 12" open daylight
- 10" bore clamp cylinder
- 6" stroke
- 64 IPM closing speed
- 64 IPM pressing speed
- 100 IPM opening speed
- Weight: 2,050 lbs.
- Dimensions: 45" w x 28" d x 44" h

## features

- Low friction rods and bushings
- Built in lift truck tubes
- Class 10,000 clean room compatible
- ViewPoint control system including:
  - Allen Bradley SLC 5/03 programmable controller
  - PanelView 550 touch screen
  - Closed-loop control of clamp pressure (including load cell)
  - Closed-loop control of platen temperature
- Ammeters for heater burnout detection (not pictured)
- Yokagawa six channel chart recorder (not pictured) including:
  - Data collection of platen temperature
  - Data collection of clamp force



## Wabash MPI

1569 Morris St., P.O. Box 298, Wabash, IN 46992-0298 USA

Phone: 260-563-1184 Fax: 260-563-1396

Email: [wabashmpi@acscorporate.com](mailto:wabashmpi@acscorporate.com), Internet: [www.wabashmpi.com](http://www.wabashmpi.com)

All data subject to change without notice ©2019 Wabash MPI

**ISO 9001:2015**  
Certified

