

SMARTDAC+ GX10 & GX20™ Data Acquisition System

features

- Color touch screen
- Data display formats
 - Trend
 - Bar Graphs
 - Digital
- USB port(s). One on the front panel and one on the rear panel
 - Connect a keyboard, mouse or USB memory drive
 - 500 MB internal memory
 - Example: Record 30 channels of data every minute would equal an approximate sample time of 2.5 years
- External SD Card (up to 32 GB)
- The recorder's setup and configuration data can be backed up and saved to the SD card or a USB memory stick
- Ethernet Communication
 - Recorded data files can be automatically transferred to a FTP Server
 - Web Server - Live data can be viewed from a network computer
 - Printer Output - Print snapshot data to a network printer
 - With an added wireless router live data can be viewed on smart phone or tablet
- Free Universal Viewer software available
 - View recorded data
 - Export recorded data to Excel



smart functionality

- Security functions can be setup to allow authorized users to specific recorder features
- Batch function
 - Record data based on batch number and lot number
 - Batch name and comments can be entered
- Report function
 - Basic report templates can be used to output Excel or PDF files
- Recorded data security
 - Recorded data stored in encrypted binary format and cannot be modified
 - The data recorder and the viewer software do not allow a data file to be overwritten by a user or automatically
- A screen snapshot can be taken and saved to the SD card



Wabash MPI

1569 Morris St., P.O. Box 298, Wabash, IN 46992-0298 USA
Phone: 260-563-1184 Fax: 260-563-1396

Email: wabashmpi@acscorporate.com, Internet: www.wabashmpi.com

All data subject to change without notice

©2019 Wabash MPI

ISO 9001:2015
registered

