



GT30-12-X

specifications

- **Clamp Specifications:**
- 5-30 ton compression force (adjustable)
- 12" L-R x 12" F-B fully guided unheated platens
- 6"- 12" open daylight
- 5" bore JIC style clamp cylinder
- 6" stroke
- 155 IPM closing speed
- 10 IPM pressing speed
- 150 IPM opening speed
- **Transfer System:**
- 12 ton transfer force
- 15" transfer stroke
- 220 IPM extend
- 20 IPM press
- 240 IPM retract
- Weight: 2,900 lbs.
- Dimensions: 41" w x 73" h x 53" d

features

- Self-contained hydraulic system
- "Mini" ViewPoint control system including:
 - Allen Bradley Micrologic 1200 programmable controller
 - PanelView 550 touch screen
 - Open-loop control of clamp pressure
 - Open-loop control of transfer pressure
- Proximity switches to control "slow close" position and "cycle reset"
- Opto-touch buttons for activation of clamp and transfer functions
- Light and curtain in front of work area with perforated metal and perimeter guarding
- Non-fused disconnect



Wabash MPI

1569 Morris St., P.O. Box 298, Wabash, IN 46992-0298 USA

Phone: 260-563-1184 Fax: 260-563-1396

Email: wabashmpi@corpemail.com, Internet: www.wabashmpi.com

CARVER

All data subject to change without notice © 2012 Wabash MPI